



ThermoLazer 300TC

THERMOLAZER™ 300TC

APPLICATIONS & MATERIALS

The ThermoLazer 300TC with its 135 kg material kettle allows more striping and less time spent refilling with material, while its' EasyGlide™ Wheel Mount System makes this unit as easy to maneuver as a LineLazer.

FEATURES & BENEFITS

SmartDie™ II System

> Delivers excellent line quality with exclusive deep-die, all steel construction and a no-tools change-out design

135 kg Material Kettle

> Easy-to-fill kettle with PaddleMax™ Dual mixer for improved mixing

40 kg Bead Hopper

> Perfectly matched to the material kettle with a superior flow design

Direct Heat System

> Direct flames and an on-board hand torch deliver maximum heat, resulting in maximum material flow

Adjustable Handle

> Handle easily adjusts to multiple heights

Adjustable Front Pointer

> Easily adjusts for all size dies for following all marks and creating straight lines

Bead Dispenser

> 30 cm dispenser with 2.5 cm increments allows you to "dial-in" the drop rate



THERMOLAZER™ 300TC

SPECIFICATIONS

ThermoLazer 300TC



Specifications

Part Number - unit only	24H622
Fuel	LP Gas (LP Tank not included)
Die Heater System	Tri-Flame
Main Burners	30,000 BTU
Material Capacity – kg (lb)	135 (300)
Melt Time for Full Capacity Thermoplastic	4-4.5 Hours without Premelt System
Melt Chamber	Single
Bead Hopper Capacity – kg (lbs)	40 (90)
Weight – kg (lbs)	133 (295)

Features

Dies available (*)	SmartDie™ II
Temperature Limit Control	N/A
Electronic Ignition	✓
Torch	✓
LineDriver™	Optional
External 4-torch Die Heat System	Optional
Internal Mixing Paddles	Dual PaddleMax™ System
Hopper Lid System	Flat, Dual Lid
Bead Dispense System	30 cm with 2.5 cm Doors

FOR MORE INFO

WWW.GRACO.COM/STRIPING

