



ThermoLazer ProMelt

# THERMOLAZER™ PROMELT

## APPLICATIONS & MATERIALS

Only Graco's breakthrough technology allows you to melt 135 kg of thermoplastic on-board in less than an hour. It's like having a premelter on wheels without the cost. Finally a solution for melting and applying thermoplastic without the hassle and cost of premelters.

## FEATURES & BENEFITS

### ProMelt™ Technology

- > 4 Chamber Melting System—More surface area to melt thermoplastic fast
- > 100,000 BTUs—Faster melt time means more jobs get done everyday

### SmartDie™ II System

- > Delivers excellent line quality with exclusive deep-die, all steel construction and a no-tools change-out design

### 135 kg Material Kettle

- > Easy-to-fill four chamber QuadMelt™ kettle system for improved heat transfer and mixing

### 40 kg Bead Hopper

- > Perfectly matched to the material kettle with a superior flow design

### Adjustable Handle

- > Handle easily adjusts to multiple heights

### Adjustable Front Pointer

- > Easily adjusts for all size dies for following all marks and creating straight lines

### Bead Dispenser

- > 30 cm dispenser with 2.5 cm increments allows you to "dial-in" the drop rate



# THERMOLAZER™ PROMELT

## SPECIFICATIONS

**ThermoLazer ProMelt**



### Specifications

|   |                                  |
|---|----------------------------------|
| Part Number - unit only                   | 24H624                           |
| Fuel                                      | LP Gas<br>(LP Tank not included) |
| Die Heater System                         | Tri-Flame                        |
| Main Burners                              | 100,000 BTU                      |
| Material Capacity – kg (lb)               | 135 (300)                        |
| Melt Time for Full Capacity Thermoplastic | Less than 1 Hour                 |
| Melt Chamber                              | QuadMelt™                        |
| Bead Hopper Capacity – kg (lbs)           | 40 (90)                          |
| Weight – kg (lbs)                         | 157 (345)                        |

### Features

|                                  |                            |
|----------------------------------|----------------------------|
| Dies available (*)               | SmartDie™ II               |
| Temperature Limit Control        | 475° F Switch              |
| Electronic Ignition              | ✓                          |
| Torch                            | ✓                          |
| LineDriver™                      | Optional                   |
| External 4-torch Die Heat System | Standard                   |
| Internal Mixing Paddles          | QuadMix System             |
| Hopper Lid System                | Raised, Single Lid         |
| Bead Dispense System             | 30 cm<br>with 2.5 cm Doors |

FOR MORE INFO

[WWW.GRACO.COM/STRIPING](http://WWW.GRACO.COM/STRIPING)

